Environmental Reference Page Guide

146 Location _____ Date _____

Project / Client _____

147

The manufacturers of "Rite in the Rain" all-weather writing products are grateful to the numerous environmental experts who have contributed to the development of this book. Should you have any additions, improvements or corrections for future publications of this field book or have suggestions for other environmental field book formats, we welcome your input.

Although much effort has been taken to insure the accuracy of the following reference pages, the J. L. Darling Corp. can not guarantee the accuracy of the data contained herein.

To provide input or solicit pricing on these or custom printed field books, contact your "Rite in the Rain" dealer or J. L. Darling Corp., 253-922-5000 or fax 253-922-5300.

Common Field Data Error Codes

Error Codes Are Used to Explain Common Mistakes and Are Written Above or Close to the Mistake
Commonly Used Error Codes Include:

- RE Recording Error
- CE Calculation Error
- TE Transcription Error
- SE Spelling Error
- CL Changed for Clarity
- DC Original Sample Description Changed After Further Evalutation
- WO Write Over
- NI Not Initialled and Dated at Time of Entry
- OB Not Recorded at the Time of Initial Observation

Note: Error Code Should Be Circled When Recorded

Hazard Classifications

Class 1 Explosives
Class 2 Gas
Class 3 Flammable Liquid
Class 4 Flammable Solids (Potential spontaneous combustion, or emission of flammable gases when in contact with water)
Class 5 Oxidizing Substances and Organic Peroxides
Class 6 Toxic (poisonous) and infectious substances
Class 7 Radioactive material
Class 8 Corrosives
Class 9 Miscellaneous dangerous goods

Container type abbreviations (for sampling guidelines):

BR - Boston Round
ABR - Amber Boston Round
AJ - Amber Jug
CWM - Clear Wide Mouth
AWM - Amber Wide Mouth
Poly - Polyethylene Bottles
BOD Bottle

148

All of these guidelines are subject to change. Always refer to the EPA or SW methods for confirmation. This is meant only as a general guide for environmental sampling. Rev. 12/95

Sampling Guidelines (liquids)

Parameters	Volume	EPA Method Water/Wastewater	Container	Preservative	Holding Times
acidity	100 ml	305	Poly	Cool @ 4 c	14 days
Alkalinity	100 ml	310	Poly	Cool @ 4 c	14 days
Ammonia	400 ml	350	Poly	pH<2 H_2SO_4 4 c	28 days
Asbestos (Drinking Water)	2 l	6004/9-83-043	ABR	4 c	48 hours
Biochemical Oxygen Demand	1 l	405.1	Poly	Cool @ 4 c	48 hours
Bromide	100 ml	320.1	Poly	none required	28 days
Chemical Oxygen Demand	50 ml	410	Poly	pH<2 H_2SO_4 4 c	28 days
Chloride	50 ml	300.0, 325	Poly	none required	28 days
Chlorine total residual	200 ml	330	Poly	none required	anal immed
Color	50 ml	110	Poly	Cool @ 4 c	48 hours
Cyanide total & amenable	500 ml	335.2, 335.1	Poly	(5) pH>12 NaOH, 0.6g Ascb, 4dch c	14 days
Fluoride	300 ml	300.0, 340	Poly	none required	28 days
Hardness	100 ml	130	Poly	pH<2 HNO_3/H_2SO_4	6 months
Hydrogen ion (pH)	25 ml	150	Poly	none required	anal immed
Kjeldahl & Organic Nitrogen	500 ml	351	Poly	pH<2 H_2SO_4 4 c	28 days
Chromium VI	200 ml	218.4, 218.5	Poly	Cool @ 4 c	24 hours
Mercury	100 ml	245	Poly	pH<2 HNO_3 (aqua regia HCl/HNO3)	28 days
Metals	200 ml	200 series/200.7	Poly	pH<2 HNO_3	6 months
Nitrate	100 ml	300.0, 352.1	Poly	Cool @ 4 c	48 hours
Nitrate-Nitrite	100 ml	300.0, 353	Poly	pH<2 H_2SO_4 4 c	28 days
Nitrite	50 ml	300.0, 354.1	Poly	Cool @ 4 c	48 hours
Oil & Grease	1 l	413	ABR	pH<2 H_2SO_4/HCl, 4 c	28 days
Organic Carbon(TOC)	25 ml	415	Poly	pH<2 HCl/H_3PO_4 4 c	28 days
Oxygen, dissolved (Combo)	300 ml	360.1	BOD BtL	none required	anal immed
Oxygen, dissolved (winkler)	300 ml	360.2	BOD BtL	(3) fix on site/dark	8 hours
Petrol. Hydrocarbons(TRPH)	1 l	418.1	AWM	pH<2 H_2SO_4/HCl, 4 c	28 days
Phenolics	500 ml	420	BR	pH<2 H_2SO_4 4 c	28 days
Phosphorus, Hydrolyzable	50 ml	365.2	Poly	pH<2 H_2SO_4 4 c	48 hours
Phosphorus, Orthophosphate	50 ml	300.0, 365.2	Poly	filter immed. 4 c	48 hours
Phosphorus, total	50 ml	365.2	Poly	pH<2 H_2SO_4 4 c	28 days
Phosphorus, total dissolved	50 ml	365.2	Poly	Filter, pH<2 H_2SO_4 4 c	24 hours
Residue, total	100 ml	160.3	Poly	Cool @ 4 c	7 days
Residue, filterable (TDS)	100 ml	160.1	Poly	Cool @ 4 c	7 days
Residue, Non filterable (TSS)	100 ml	160.2	Poly	Cool @ 4 c	7 days
Residue, settleable	1 l	160.5	AJ	Cool @ 4 c	48 hours
Residue, Volatile	100 ml	160.4	Poly	Cool @ 4 c	7 days
Silica	50 ml	370.1	Poly	Cool @ 4 c	28 days
Specific Conductance	100 ml	120.1	Poly	Cool @ 4 c	28 days
Sulfate	50 ml	300.0	Poly	Cool @ 4 c	28 days
Sulfide	500 ml	376	Poly	pH>9 NaOH, ZnOAc, 4 c	7 days
Sulfite	50 ml	377.1	Poly	none required	anal immed
Surfactants (MBAS)	250 ml	425.1	Poly	Cool @ 4 c	48 hours
Temperature	1 l	170.1	Poly	none required	anal immed
Turbidity	100 ml	180.1	Poly	Cool @ 4 c	48 hours
Purgeable Halocarbons	5 ml	601, 624	GV	(1) .008% $Na_2S_2O_3$ 4 c	14 days
Purgeable aromatic Hyd. carb.	5 ml	602, 624	GV	(1) pH<2 HCl, $Na_2S_2O_3$ 4 c	14 days
Acrolein & Acrylonitrile	5 ml	603	GV	(1) pH 4-6, $Na_2S_2O_3$ 4 c	14 days
Phenols	1 l	604	AJ	(1) .008% $Na_2S_2O_3$ 4 c	7 days
Benzidines	1 l	605	AJ	(1) .008% $Na_2S_2O_3$, in prime lens	7 days
Phthalate Esters	1 l	606	AJ	Cool @ 4 c	7 days
Nitrosamines	1 l	607	AJ	(1) $Na_2S_2O_3$ 4 c dark, pH<10	7 days
PCB's	1 l	608	AJ	Cool @ 4 c	7 days
Pesticides, Chlorinated	1 l	608	AJ	(5) pH 5-9, Sodi 4 c, $Na_2S_2O_3$	7 days
Nitroaromatics & Isophorone	1 l	609	AJ	4 c	7 days

149

Parameters	Volume	Water/Wastewater	Container	Preservative	Times
Polynuclear Aromatic Hydcarbn	1 l	610	AJ	(1) $Na_2S_2O_3$ 4 c Dark	7 days
Haloethers	1 l	611	AJ	(1) .008% $Na_2S_2O_3$ 4 c	7 days
Chlorinated Hydrocarbons	1 l	612	AJ	Cool 4 c	7 days
Chlorinated Herbicides	1 l	6640/(SM 17th Ed.)	AJ	(1) Cool 4 c, .008% $Na_2S_2O_3$	7 days
Dioxins & Furans	1 l	613, 1613	AJ	(1) .008% $Na_2S_2O_3$ 4 c	7 days
Pesticides, Organophosphorus	1 l		AJ	(1) pH 5-9, Dark 4 c, .008% $Na_2S_2O_3$	7 days
Radiological test, gross A & B	1 l		Poly	pH<2 HNO_3	6 months
Radium (Total)	1 l		Poly	pH<2 HNO_3	6 months
Coliform, Fecal & Total	100ml	9221, 9222-SM 17th	Poly	(1) .008% $Na_2S_2O_3$ 4 c	6 hours
Fecal Streptococci	100ml	9230 (SM 17th Ed.)	Poly	(1) .008% $Na_2S_2O_3$ 4 c	6 hours
Nonhalogenated volatile orgnic	5 g		GV/cor	(Grab HCl, cool 4 c, .008% $Na_2S_2O_3$)	14 days
Volatile Organics	5 ml	624,1624	GV/cor	(Grab HCl, cool 4 c, .008% $Na_2S_2O_3$)	14 days
Semi Volatile Organics	1 l	625, 1625	AJ	(1) Cool 4 c, .008% $Na_2S_2O_3$	7 days
TCLP Extctn (Haz Waste Tox)	4 l		AJ	None	7 days
Haz Waste Corrosivity	2 l		AJ	None	7 days
Haz Waste Ignitability	100ml		BR	None	7 days
Haz Waste Rctvty-Cyn/Sulf	250ml		Poly	Cool @ 4 c Dark	7 days

Sampling Guidelines (Solids)

Parameters	Volume	Method Solid Waste	Container	Holding Times
Hydrogen ION (pH)	20 g	9040,9045	CWM	anal lmed.
Chromium VI	2 g	7196,7197	CWM	24 Hours
Mercury	2 g	7470,7471	CWM	sup(ignkDPE)
Metals (exqt Chromium VI&Hg)	2 g	7000 Series/6010	CWM	6 months
Nitrate	50 g	9200	CWM	48 hours
Oil & Grease	20 g	9070,9071	CWM	28 days
Organic Carbon (TOC)	10 g	9060	CWM	28 days
Phenolics		9065		28 days
Sulfate		9038		28 days
Sulfide		9030		7 days
Purgeable Halocarbons	5 g	8010,8240	CWM	14 days
Purgeable Aromatic Hydrcbns	5 g	8020	CWM	14 days
Acrolein & Acrylonitrile	5 g	8030	CWM	14 days
Phenols	30 g	8040, 8270	CWM	7 days(40 days AE)
Benzidines	30 g	8270	CWM	7 days(40 days AE)
Phthalate Esters	30 g	8060,8270	CWM	7 days(40 days AE)
Nitrosamines	30 g	8270	CWM	7 days(40 days AE)
PCB's	30 g	8080	CWM	*
Pesticides	30 g	8080	CWM	*
Nitroaromatics & Isophorone	30 g	8090, 8270	CWM	*
Polynuclear Aromatic Hydrcbn	30 g	8100, 8270, 8310	CWM	*
Haloethers	30 g	8270	CWM	*
Chlorinated Hydrocarbons	30 g	8120, 8270	CWM	*
Chlorinated Herbicides	50 g	8150	CWM	*
Dioxins & Furans	10 g	8280, 8290	CWM	*
Total Organic Halogens(TOX)		9020		7 days
Pesticides, Organophosphorus	30 g	8140	CWM	7days(40 days AE)
Radiological Test, Gross A&B		9310		6 months
Radium (Total)		9315,9320		6 months
Coliform, Fecal & Total		9131, 9132		6 hours
Nonhalogenated Volatile Organic	5 g	8015, 8240	CWM	14 days
Volatile Organics	5 g	8240	CWM	14 days
Semi Volatile Organics	30 g	8270	CWM	7 days(40 days AE)
TCLP Extctn (Haz Waste Tox)	300g	1311	CWM	7 days
Haz Waste Corrosivity		1110		7 days
Haz Waste Ignitability		1010, 1020		7 days
Haz Waste Reactivity-Cyn/Sulf	10 g	7.3.3.2, 7.3.4.2	CWM	7 days

150

Approximate Volume of Water in Casing or Hole

Diameter of Casing or Hole (in.)	Gallons Per Foot of Depth	Cubic Feet Per Foot of Depth	Liters Per Meter of Depth	Cubic Meters Per Meter of Depth
1	0.041	0.0055	0.509	0.509×10^{-3}
1½	0.092	0.0123	1.142	1.142×10^{-3}
2	0.163	0.0218	2.204	2.024×10^{-3}
2½	0.255	0.0341	3.167	3.167×10^{-3}
3	0.367	0.0491	4.558	4.558×10^{-3}
3½	0.500	0.0668	6.209	6.209×10^{-3}
4	0.653	0.0873	8.110	8.110×10^{-3}
4½	0.826	0.1104	10.26	10.26×10^{-3}
5	1.020	0.1364	12.67	12.67×10^{-3}
5½	1.234	0.1650	15.33	15.33×10^{-3}
6	1.469	0.1963	18.24	18.24×10^{-3}
7	2.000	0.2673	24.84	24.84×10^{-3}
8	2.611	0.3491	32.43	32.43×10^{-3}
9	3.305	0.4418	41.04	41.04×10^{-3}
10	4.080	0.5454	50.67	50.67×10^{-3}
11	4.937	0.6600	61.31	61.31×10^{-3}
12	5.875	0.7854	72.96	72.96×10^{-3}
14	8.000	1.069	99.33	99.35×10^{-3}
16	10.44	1.396	129.65	129.65×10^{-3}
18	13.22	1.767	164.18	164.18×10^{-3}
20	16.32	2.182	202.68	202.68×10^{-3}
22	19.75	2.640	245.28	245.28×10^{-3}
24	23.50	3.142	291.85	291.85×10^{-3}
26	27.58	3.687	342.52	342.52×10^{-3}
28	32.00	4.276	397.41	397.41×10^{-3}
30	36.72	4.909	456.02	456.02×10^{-3}
32	41.78	5.585	518.87	518.87×10^{-3}
34	47.16	6.305	585.68	585.68×10^{-3}
36	52.88	7.069	656.72	656.72×10^{-3}

Permanent Monitoring Well

1 Gallon water weighs 8.33 lbs. = 3.785 Kg
1 Liter water weights 1 Kg = 2.205 lbs
1 Gallon per foot of depth = 12.419 liters per foot of depth
1 Gal per M of depth = 12.419×10^{-3} cu M per M of depth

$V = \pi R^2 H$ (Volume of a Cylinder)

standing water = (depth to water) - (depth of well)
water column = (water level) - (water depth)
water column vol(Gal) = (water column) x (casing diameter factor)

Source: Nielson Environmental Field School, Galena, OH

151

Schedule 40 PVC Pipe

Nominal size	Max PSI at 74° F	OD	ID	Nominal Wall	Nominal Weight per 100
1/2"	600	0.840"		0.109"	16.2Lbs
3/4"	480	1.050"	0.824"	0.113"	21.5Lbs
1"	450	1.315"	1.049"	0.133"	32.9Lbs
1 1/4"	370	1.660"	1.380"	0.140"	43.4Lbs
1 1/2"	330	1.900"	1.610"	0.145"	51.9Lbs
2"	280	2.375"	2.067"	0.154"	69.8Lbs
2 1/2"	300	2.875"	2.469"	0.203"	111.0Lbs
3"	260	3.500"	3.068"	0.216"	145.0Lbs
4"	220	4.500"	4.026"	0.237"	206.0Lbs
5"	n/a	5.563"	5.047"	0.258"	277.0Lbs
6"	180	6.625"	6.065"	0.280"	363.0Lbs
8"	160	8.625"	7.981"	0.332"	563.0Lbs
10"	140	10.750"	10.020"	0.365"	775.0Lbs
12"	130	12.750"	11.938"	0.406"	1030.0Lbs

Schedule 80 PVC Pipe

Nominal Size	Max PSI at 74°	OD	ID	Nominal Wall	Nominal weight per 100
1/2"	850	0.840"	0.546"	0.147"	20.6Lbs
3/4"	690	1.050"	0.742"	0.154"	28.0Lbs
1"	630	1.315"	0.957"	0.179"	41.3Lbs
1 1/4"	520	1.660"	1.278"	0.191"	57.1Lbs
1 1/2"	470	1.900"	1.500"	0.200"	69.2Lbs
2"	400	2.375"	1.939"	0.218"	95.6Lbs
2 1/2"	420	2.875"	2.323"	0.276"	146.0Lbs
3"	370	3.500"	2.900"	0.300"	198.0Lbs
4"	320	4.500"	3.826"	0.337"	286.0Lbs
5"	n/a	5.563"	4.768"	0.375"	392.0Lbs
6"	280	6.625"	5.761"	0.432"	546.0Lbs
8"	245	8.625"	7.625"	0.500"	830.0Lbs
10"	230	10.750"	9.564"	0.593"	1230.0Lbs
12"	230	12.750"	11.376"	0.687"	1690.0Lbs

152

Soil Classification

	mm	inches	Sieve Sizes
Boulders	>300	>11.8	-
Cobbles	75-300	2.9-11.8	-
Coarse Gravel	75-19	2.9-.75	-
Fine Gravel	19-4.8	.75-.19	3/4" - No. 4
Coarse Sand	4.8-2.0	.19-.08	No. 4 - No. 10
Medium Sand	2.0-.43	.08-.02	No. 10 - No. 40
Fine Sand	.43-.08	.02-.003	No. 40 - No. 200
Fine silt & clay	< .08	< .003	< No. 200

Clay

Clay Consistency	Thumb: Penetration	SPT, N Blows/Ft.	Undrained shearength c (FSE) Torvane	Unconfined compressive Strength q Pocket Penetrometer
Very Soft	Penetrated several inches by thumb: exudes between thumb and fingers when squeezed in hand.	<2	250	500
Soft	Penetrated one inch by thumb. Molded by light finger pressure.	2-4	250-500	500-1000
Medium Soft	Penetrated over 1/4" by thumb with moderate effort. Molded by strong finger pressure.	4-8	500-1000	1000-2000
Stiff	Indented 1/4" with thumb, but only penetrated with great effort.	8-15	1000-2000	2000-4000
Very Stiff	Readily indented by thumnail.	15-30	2000-4000	4000-8000
Hard	Indented only with difficulty, by thumnail.	>30	>4000	>8000

Sand

Soil Type	SPT N Blows/Ft.	Relative Density%	Field Test
Very Loose Sand	4	0-15	Easily Penetrated with 1/2" rod pushed by hand.
Loose Sand	4-10	15-35	Easily penetrated with 1/2" rod pushed by hand.
Med. Dense Sand	10-30	35-65	Penetrated a foot with 1/2" rod driven with 5lb hammer.
Dense Sand	30-50	65-85	Penetrated a foot with 1/2" rod driven with a 5lb hammer
Very Dense Sand	50	85-100	Penetrated inches with a 1/2" rod driven by 5lb hammer.

153

Soil Classification

Coarse grained Soils More than 50% retained on No. 200 sieve	Gravel: More than half of coarse fraction is larger than No. 4 sieve size	Clean gravels (Little or no fines)	GW	Well-graded gravels, gravel-sand mixtures, little or no fines
			GP	Poorly-graded gravels, gravel sand mixtures, little or no fines
		Gravels with fines (Appreciable amount of fines)	GM	Silty gravels, gravel-sand-silt mixtures
			GC	Clayey gravels, gravel-sand-clay mixtures
	Sands: More than half of coarse fraction is smaller than No. 4 sieve size	Clean sands (Little or no fines)	SW	Well-graded sands, gravelly sands, little or no fines
			SP	Poorly graded sands, gravelly sands, little or no fines
		Sands with fines (Appreciable amount of fines)	SM	Silty sands, sand-silt mixtures
			SC	Clayey sands, sand-clay mixtures
Fine grained Soils More than 50% passes smaller than No. 200 sieve	Silts and Clays Liquid limit less than 50		ML	Inorganic silts and very fine sands, rock flour, silty or clayey fine sands or clayey silts with slight plasticity.
			CL	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
			OL	Organic silts and organic silty clays of low plasticity
	Silts and Clays Liquid limit greater than 50		MH	Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts
			CH	Inorganic clays of high plasticity, fat clays
			OH	Organic clays of medium to high plasticity, organic silts
	Highly Organic		Pt	Peat and other highly organic soils

154

MEASUREMENT CONVERSIONS

INCH CM

IF YOU KNOW	MULTIPLY BY	TO FIND
LENGTH		
inches	2.540	centimeters
feet	30.480	centimeters
yards	0.914	meters
miles	1.609	kilometers
millimeters	0.039	inches
centimeters	0.393	inches
meters	3.280	feet
meters	1.093	yards
kilometers	0.621	miles
WEIGHT		
ounces	28.350	grams
pounds	0.453	kilograms
grams	0.035	ounces
kilograms	2.204	pounds
VOLUME		
fluid ounces	29.573	milliliters
pints	0.473	liters
quarts	0.946	liters
gallons (U.S.)	3.785	liters
milliliters	0.033	fluid ounces
cubic inches	0.01639	liters
cubic inches	0.0043	gallons
TEMPERATURE		
°C×(°F - 32) x .555		°F = 1.8(K - 273.15) +32
°F=(°C x 1.8) + 32		K°=C + 273.15
C°=K - 273.15		K°= 0.555(F + 273.15) - 32

Inches	Decimals of Inch	Millimeters
1/16	.0052	1.5875
1/8	.0104	3.1750
3/16	.0156	4.7625
1/4	.0208	6.3500
5/16	.0260	7.9350
3/8	.0313	9.5250
1/2	.0417	12.700
5/8	.0521	15.875
3/4	.0625	19.050
7/8	.0729	22.225
1"	.0833	25.400
2"	.1667	50.800
3"	.2500	76.200
4"	.3333	101.60
5"	.4167	127.00
6"	.5000	152.40
7"	.5833	177.80
8"	.6667	203.20
9"	.7500	228.60
10"	.8333	254.00
11"	.9167	279.40
1 foot	1.0000	304.80

155

Additional Conversions

Concentrations

mg/L = 1000.30 ppb
mg/L = 1.00030 ppm
ppb = 0.00100 mg/L
ppm = .99970 mg/L
mg/L = (0.00245 x cu.ft./sec.) tonnes/day
mg/L = (0.0000864 x L/sec.) tonnes/day
mg/L = (0.00270 x cu.ft./sec.) tons/day
tons/day = (370.79782÷cu.ft./sec.) mg/L
tonnes per day = (408.73452÷cu.ft./sec) mg/L
tonnes per day = (11574.07407÷L/sec.) mg/L

Volume/ Flow or Time

Cubic ft./sec. = 1.98347 Acre ft./day
Cubic ft./sec. = 0.64632 Million gallons/day
Cubic ft./sec. = 448.83117 Gallons/min.
Cubic ft./sec. = 0.02832 Cubic meters/sec.
Cubic ft./sec. = 28.31685 Liters/sec.
Cubic ft./sec. = 373.73 Imperial gallons/min.

Gallons/min. = 0.00223 Cubic ft./sec.
Gallons/min. = 6.309×10^{-5} Cubic meters/sec.
Gallons/min. = 0.06309 Liters/sec.

Cubic meters/sec. = 1000.00012 Liters/sec
Cubic meters/sec. = 35.31467 Cubic ft./sec.

Liters/sec. = 0.001 Cubic meters/sec.
Liters/sec. = 0.03531 Cubic ft./sec.
Liters/sec. = 15.85032 Gallons/min.

Million gallons/day = 1.54723 Cubic ft./sec.
Million gallons/day = 3.06888 Acre ft./day

Acre ft./day = 0.504167 Cubic ft./sec.
Acre ft./day = 0.325851 Million gallons/day

Velocity

ft./sec. = 0.304800 m/s
ft./sec. = 0.681818 mph
km/hr. = 0.277778 m/s
km/hr. = 0.621371 mph

Acceleration

ft./s/s = 0.304600 m/s/s
m/s/s = 3.280640 ft./s/s

156

Maximum Concentration of Contaminants for the Toxicity Characteristic

EPA HW NUMBER	CONTAMINANT	REGULATORY LEVEL (mg/L)	ANALYTE CATEGORY
D004	Arsenic	5.0	Metal
D005	Barium	100.0	Metal
D018	Benzene	0.5	Volatile
D006	Cadmium	1.0	Metal
D019	Carbon tetrachloride	0.5	Volatile
D020	Chlordane	0.03	Pesticide
D021	Chlorobenzene	100.0	Volatile
D022	Chloroform	6.0	Volatile
D007	Chromium	5.0	Metal
D023	o-Cresol	200.0	Acid Extractable
D024	m-Cresol	200.0	Acid Extractable
D025	p-Cresol	200.0	Acid Extractable
D026	Cresol	200.0	Acid Extractable
D016	2,4-D	10.0	Pesticide
D027	1,4-Dichlorobenzene	7.5	Base Neutral
D028	1,2-Dichloroethane	0.5	Volatile
D029	1,1-Dichloroethylene	0.7	Volatile
D030	2,4-Dinitrotoluene	0.13	Base Neutral
D012	Endrin	0.02	Pesticide
D031	Heptachlor (and its hydroxide)	0.008	Pesticide
D032	Hexachlorobenzene	0.13	Base Neutral
D033	Hexachlorobutadiene	0.5	Base Neutral
D034	Hexachloroethane	3.0	Base Neutral
D008	Lead	5.0	Metal
D013	Lidane	0.4	Pesticide
D009	Mercury	0.2	Metal
D014	Methoxychlor	10.0	Pesticide
D035	Methyl ethyl ketone	200.0	Volitle
D036	Nitrobenzene	2.0	Base Neutral
D037	Pentachlorophenol	100.0	Acid Extractable
D038	Pyridine	5.0	Base Neutral
D010	Selenium	1.0	Metal
D011	Silver	5.0	Metal
D039	Tetrachoroethylene	0.7	Volatile
D015	Toxaphene	.05	Pesticide
D040	Trichlorcethylene	.05	Volatile
D041	2,4,5-Trichlorophenol	400.0	Acid Extractable
D042	2,4,6-Trichlorophenol	2.0	Acid Extractable
D017	2,4,5-TP (Silvex)	1.0	Pesticide
D043	Vinyl chloride	.02	Volatile

Hazardous Waste Number

4 9

Phone List:

Emergency Numbers:

National Response Center - 1 - 800 - 424 - 8802
Fire -
Ambulance -
Poison Control -

Additional Numbers:

J. L. DARLING CORPORATION
E-mail: sales@riteintherain.com • www.riteintherain.com
2614 PACIFIC HWY. E. • TACOMA, WA 98424-1017 • (253) 922-5000 • FAX (253) 922-5300